Standard tile sizes
300 x 300 x 9 mm (12" x 12")
388 x 388 x 9 mm (15" x 15")

Weight per sq metre: approx 18 kg

Made to order: 7 weeks

These products have been certified in accordance with ISO quality standards by independent authorised laboratories. Maintenance free, they are extremely durable, easy to clean and have anti-slip, non-combustible and knock-resistant characteristics.

TECHNICAL INFORMATION (Abridged)

Product Type	Porcelain / Quartzite floor and wall tiles	
Finishes and Suitability		
Finishes Available	Matt, Satin.	
Suitability	Interior/Exterior use for floors, walls and cladding.	
Areas of Use - Product Suitability		
Domestic	Kitchens, bathrooms, conservatories, etc	YES
Residential	Hotels, Housing, etc	YES
Public Areas/High traffic	Restaurants, offices, shops, pavements, etc	YES

		TEST STANDARDS
Resistance to slip	**= R_d = 65 (Class 3)** (top rating)	**UNE-ENV1 2633 ISO/DIS 10545-17**
Resistance to Surface Abrasion All Colours: PEI Rating	= 4	**EN ISO 10545-07**
Surface Hardness All Colours: MoHs rating	= 6 (Conforms)	**EN 101**
Water Absorption All colours: Conforms (acc to test criteria)		**EN ISO 10545-03**
Acid & Alkali Resistance All colours: Results GLC (Acids, Alkalis) All colours: Results GB (Household)	(Conforms) (Conforms)	**EN ISO 10545-13**
Frost Resistance All Colours: Resistant (acc to test criteria)	(Conforms)	**EN ISO 10545-12**
Impact resistance by measurement of coefficient of restitution	(Conforms)	**EN ISO 10545-5**
Thermal Expansion	= $6.4*10^{-6}$/°C (Conforms)	**EN ISO 10545-8**

COLLECTIONS

DESIGN

WWW.CRINSON.COM

BESPOKE PHOTOGRAPHIC DESIGN

WWW.DIGITILE.CO.UK

For more information, please call
+44 (0)1622 804 808
contact@digitile.co.uk / contact@crinson.com
www.digitile.co.uk | www.crinson.com